



60" Gas Ranges

Wolf has perfected the form, function and sheer durability of our gas ranges. Wolf gas ranges offer standard features such as an infrared oven broiler, convection baking, dual brass surface burners and our signature large red control knobs. Optional infrared charbroiler, infrared griddle and French Top give you the freedom to customize your gas range.



Model R606F shown with 5" riser. Also shown is Model W602418R Pro wall hood and Model WWD30 warming drawer.



Model R606DG



Model R606F



Model R606CG

Features

- Natural or LP gas models
- Classic stainless steel exterior finish
- Optional infrared charbroiler, infrared griddle and French Top configurations
- Distinctive red control knobs with chrome bezels—black knobs optional
- Dual brass burners with automatic reignition at all settings
- Porcelain-coated cast iron top grates
- Large-capacity convection oven with infrared broiler and three adjustable oven racks
- 18" oven with two adjustable racks
- Spring/damper door hinge system
- Stainless steel drip tray
- Adjustable stainless steel legs in front and rear casters
- Full side panels and skirt

Surface Features

Model	R606DG	R606F	R606CG
Surface Burners – 16,000 Btu/hr with 500 Btu/hr delivered at simmer	6	6	6
Infrared Charbroiler – 16,000 Btu/hr			■
Infrared Griddle – 18,000 Btu/hr			■
Double Griddle – 18,000 Btu/hr	■		
French Top – 15,000 Btu/hr		■	

Model numbers are for natural gas ranges, add (-LP) to the model number for LP gas.


Accessories

- Classic stainless steel risers in 5" and 10" heights, or 20" riser with shelf
- Classic stainless steel island trim
- Black control knobs
- Porcelain-coated, cast iron wok grate
- Porcelain-coated, cast iron two-burner S-grate
- Oven rack
- Hardwood cutting board (griddle models only)
- High altitude conversion kit

Accessories are available through your Wolf dealer. To obtain local dealer information, visit the Showroom Locator section of our website, wolfappliance.com.



This appliance is certified by Star-K to meet strict religious regulations in conjunction with specific instructions found on www.star-k.org.



Infrared Charbroiler



French Top



Overall Dimensions

Front View Dimensions:

- Overall Width: 60" (1524)
- Overall Depth: 28 3/8" (721)
- Overall Height to Cooking Surface: 37" (940)
- Height to Top of Cabinet: 46 3/4" (1187) WITH 10" RISER
- Height to Top of Cabinet: 56 3/4" (1441) WITH 20" RISER

Side View Dimensions:

- Overall Depth: 27 1/4" (692)
- Height to Top of Cabinet: 41 3/4" (1060) WITH 5" RISER
- Height to Top of Cabinet: 46 3/4" (1187) WITH 10" RISER
- Height to Top of Cabinet: 56 3/4" (1441) WITH 20" RISER

Other Dimensions:

- Height to Top of Cabinet: 36" (914)
- Height to Top of Cabinet: 21 1/2" (64)
- Height to Top of Cabinet: 25 1/4" (641)
- Height to Top of Cabinet: 43 3/8" (1102)

Legs and Casters Allow 1" (25) Height Adjustment

Unit dimensions may vary by $\pm 1/8"$.

Exterior Finish	Classic Stainless Steel
Overall Width	60"
Overall Height (to cooking surface)	37"
Overall Depth	28 ³ / ₈ "
Oven Interior Capacity (per oven)	4.4 cu ft
Oven Interior Dimensions (per oven)	24" W x 18 ⁵ / ₈ " H x 17" D
Opening Width	60 ¹ / ₄ "
Opening Height (to countertop)	36"
Opening Depth	24"
Electrical Requirements	110/120 V AC 50/60 Hz, 15 amp circuit
Shipping Weight	875–950 lbs

Diagram illustrating the placement of a ventilation hood and countertop relative to a rough opening and combustible materials.

Key Dimensions and Clearances:

- VENTILATION HOOD:**
 - 44" min (1118) COUNTERTOP TO COMBUSTIBLE MATERIALS
 - 30" (762) TO 36" (914) COUNTERTOP TO BOTTOM OF VENTILATION HOOD
 - 18" min (457) TO COUNTERTOP
 - 13" max (330) (Clearance to adjacent wall)
- ROUGH OPENING:**
 - 60 1/4" (1530) FINISHED ROUGH OPENING WIDTH
 - 6" min (152) TO COMBUSTIBLE MATERIALS (BOTH SIDES)
- Countertop and Hood Placement:**
 - 10" (254) and 12" (305) dimensions for countertop/hood placement.
 - 8" (203) and 5 1/2" (140) dimensions for countertop/hood placement.
 - 36" (914) and 37" (940) dimensions for countertop/hood placement.
 - 2" (51) dimension for countertop/hood placement.
 - 5" (127) dimension for countertop/hood placement.
- Gas Supply:**
 - LOCATION OF GAS SUPPLY EXTENDS 3" (76)
 - 37" (940) TO COOKING SURFACE

ISLAND INSTALLATIONS: 12" (305) MINIMUM CLEARANCE FROM BACK OF RANGE TO COMBUSTIBLE REAR WALL ABOVE COUNTERTOP – 0" (0) TO NON-COMBUSTIBLE MATERIALS

- A riser is required for installations against a combustible surface.
- A Wolf Pro wall, chimney, island ventilation hood or hood liner is recommended.
- Natural gas and LP gas installations above 8,000' require the high altitude kit.

Dimensions in parentheses are in millimeters unless otherwise specified.